



Sinotruk 6x4 Tipper truck

Truck Model		ZZ3257N3647A
Dimension(L*W*H) (unloaded) (mm)		8145*2496*3170
Cargo body size (L*W*H) (mm)		5400*2300*1500. bottom 8mm thick, side 6mm.
Hydraulic Lift System		Middle lift
Approaching angle/Departure angle (°)		19/29
Overhang(front/rear) (mm)		1500/1581
Wheel base (mm)		2925+1350
Max speed (km/h)		72
Curb weight (kg)		12,250
Rated Loading Weight (kg)		12,960
Engine (Steyr technology, made in China)	Model	WD615,cooled, four strokes, 6 cylinders in line with water cooling, turbocharged and intercooling, directly injection
	Fuel type	Diesel
	Horse Power, max (kw/rpm)	336HP
	Emission	EURO II
Fuel tanker capacity (L)		300L
Transmission	Model	HW15710, 10 forward gears, 2 reverse
Brake system	Service brake	Dual circuit compressed air brake
	Parking brake	spring energy, compressed air operating on rear wheels
Steering system	Model	ZF8098
Front axle	HF9 brake, Steering with double T-cross section beam	
Rear axle	HC16, Pressed axle housing, central double reduction with differential locks between axles and wheels	
Color available for option	White, red, Yellow.	
Tyres	12.00-20 11-wheels (incl. 1pc of backup wheel)	
Electrical system	Battery	2X12V/165Ah
	Alternator	28V-1500kw
	Starter	7.5Kw/24V
Cab	HW76 standard cab. Basic configuration for <u>single-sleeper, with air conditioner</u> , new seats; Up and down, front and rear adjustable steering wheel; European new integrated heater; With large LCD display and luxury heavy trucks in the world of synchronized Germany VDO instrumentation and electrical control module; Off-highway vehicles for a four-point full-float + spring suspension damping devices, horizontal stabilizer Double locking structure of seat belts; Outer Sun shroud. CAB standard: the cruise (common rail); Abnormal noise of generator voltage warning system (in case of electronic devices).	

The shown picture might differ from the above specifications